KODAK Products

Product Data Sheet

D-01-231-10

KODAK MAX SUPER Alkaline Battery

Effective: 19/01/2021





Dimensions are in millimetres

Chemical system:	Alkaline, MnO2 / KOH / Zn
Designations:	LR41, AG3, 384, SR41
Nominal Voltage:	1.5 V
Nominal Capacity:	38 mAh at 22 kOhms to 0.9 Volts
Weight:	0.61 g
Volume:	0.078cm^3
Recommended storage temperature:	10 – 25 °C, RH no more than 75%.
Operating temperatures:	-10 – 45 °C
Reaction:	$2MnO_2 + Zn + H_2O \rightarrow 2MnOOH + ZnO$
Terminals:	Flat contacts
Jacket:	None

Note:
1) No added Mercury / 99.9999% Mercury Free
2) No added Lead /99.999% Lead Free
3) No added Cadmium / 99.9999% Cadmium Free
4) No added PFOS (Perfluorooctane sulfonates)
5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2013/56/EU & 2006/122/EC.
6) SDS sheets are available on request from Strand Europe Ltd.

DANGER: Keep batteries out of reach of children. If swallowed, the battery can cause serious injury or death. Severe burns can occur within hours of ingestion. If you suspect that a battery has been ingested, seek immediate medical attention. Have doctor call CHEMTREC Day or Night on 1-800-424-9300 / +1 703-527-3887. **CAUTION:** Ensure that the battery compartment is completely secure, meaning closed and locked to prevent easy access by children. If the battery compartment cannot be completely secured, discontinue use of the product, or keep out of sight and reach of children. .

Brand Licensee
KODAK Batteries
KODAK LED Bulbs
KODAK Headphones
KODAK LED Flashlights

The Kodak trademark, logo and trade dress are used under license from Kodak.
© 2021 STRAND EUROPE LTD.
www.kodakbatteries.strandeurope.com

Version: 2.2

Date: 19 January 2021