



## Kodak Charger • Chargeur • Cargador

Model : K620E-C  
 Input : AC 220V - 240V ~ 50Hz 6W  
 Output : DC 2.8V  $\overline{\text{---}}$  220mA (AA size): 100mA (AAA size)

**CAUTION:** Charge only Ni-MH type rechargeable batteries. Other types of battery may burst causing personal injury and damage. Risk of injury. Risk of fire and electric shock. Dry location use only. Read instructions before charging.

**WARNING:** Use only rechargeable batteries, other types may explode.  
**AVERTISSEMENT:** Utiliser uniquement des piles rechargeables, les pile non-rechargeable risquent d'exploser. **AVISO:** Utilice únicamente baterias recargables, otros tipos pueden explotar.



Made in China for and distributed by STRAND EUROPE LTD, Strand House, Yateley, GU46 6GE, UK  
 © 2013 STRAND EUROPE LTD  
 Licensed trademark: Kodak



Designation	Kodak K620E Ni-MH Value Charger		
Dimensions	L 106 mm x W 66 mm x H 33.5 mm (without plug)		
Weight	177 g $\pm$ 10%		
Battery Size Application	AA and AAA		
Battery type	Ni-MH		
LED Indication	LED light on:	Power on, Charging	
	LED light off:	Power off, not Charging	
Input Power	220 - 240 V AC/50 Hz, 6 W max		
Output Voltage	2.8 V, DC		
Output-Charge Current	Max. 220 mA $\pm$ 10% for AA batteries		
	Max. 100 mA $\pm$ 10% for AAA batteries		
Charge Time (approx.)	Ni-MH AA (2500mAh)	1-4 batteries	13.5 hours
	Ni-MH AA (2100mAh)	1-4 batteries	11.5 hours
	Ni-MH AA (1700mAh)	1-4 batteries	9.5 hours
	Ni-MH AAA (900mAh)	1-4 batteries	11 hours
Charge Protection	Mechanical reverse polarity protection (wrong insertion)		
Compliance	1. Safety: IEC 60335-2		
	2. EMI: EN 55022, EN 55024, EN 61000-3-2 & EN 61000-3-3		
Approvals	CE, GS		

The Data in this publication represents product tested under the conditions specified. They do not represent standards or specifications which must be met. Strand reserves the right to change and improve product characteristics at any time. Contents herein do not constitute a warranty.

