



<b>Chemical system:</b>	Lithium/Iron Disulfide, Li/FeS <sub>2</sub>
<b>Designations:</b>	IEC FR03, ANSI 24LF
<b>Nominal Voltage:</b>	1.5V
<b>Nominal Capacity:</b>	1100 mAh at 75 Ohms to 0.8 Volts
<b>Internal Impedance:</b>	0.45 Ohms (typically)
<b>Average Weight:</b>	7.5 g
<b>Average Volume:</b>	3.8 cm <sup>3</sup>
<b>Recommended storage temperature:</b>	+5 – +25 °C, RH no more than 75%.
<b>Operating temperatures:</b>	-40 – +60 °C
<b>Reaction:</b>	2 Li + FeS <sub>2</sub> → Li <sub>2</sub> FeS <sub>2</sub>
<b>Terminals:</b>	Flat contacts, protruding negative
<b>Jacket:</b>	Aluminium label
<b>Lithium Content:</b>	Under 1 g

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2013/56/EU & 2006/122/EC.
- 6) SDS sheets are available on request from Strand Europe Ltd.



**Brand Licensee**

KODAK Batteries  
KODAK LED Bulbs  
KODAK Headphones  
KODAK LED Flashlights

The Kodak trademark, logo and trade dress are used under license from Kodak.  
© 2021 STRAND EUROPE LTD.  
www.kodakbatteries.strand europe.com