



Designation	Kodak USB-4 Ni-MH battery Fast Charger		
Dimensions	L 75 mm x W66 mm x H 25.2 mm		
Weight	47 g ± 10%		
Battery Size Application	AA and AAA		
Battery type	Ni-MH		
LED Indication	LED light on:	Charging on a red light, Full of green light	
	LED light off:	No battery connected/ Charge finished	
Input Power	5Vdc, 1000mA max (Via USB)		
Output Voltage	1.2 V, DC		
Output-Charge Current	Max. 1800 mA ± 10% for AA batteries*		
	Max. 900 mA ± 10% for AAA batteries*		
Charge Time	Ni-MH AA (2500mAh)	1-2 batteries	1.7-3.4 hours
	Ni-MH AA (2100mAh)	1-2 batteries	1.4-2.8 hours
	Ni-MH AA (1700mAh)	1-2 batteries	1.2-2.4 hours
	Ni-MH AAA (900mAh)	1-2 batteries	1.2-2.4 hours
Charge Protection	Mechanical reverse polarity protection (wrong insertion)		
Approvals	CE		

*For either 1 - 4 batteries, charging current is the same.

The Data in this publication represents product tested under the conditions specified. They do not represent standards or specifications which must be met. Strand reserves the right to change and improve product characteristics at any time. Contents herein do not constitute a warranty.