



Designation	KODAK USB 2 slot fast charger		
Dimensions	L 75 mm x W 36.5 mm x H 26.5 mm		
Weight	35 g ± 10%		
Battery Size Application	AA and AAA		
Battery type	Ni-MH		
LED Indication	RED LED light on:	Battery charging.	
	Green LED light on:	Battery full & unit will stop charging	
	Flashing LED	Error	
Input Power	5Vdc, 1A max (Via USB-C)		
Output Voltage	1.2 V, DC		
Output-Charge Current		AA	AAA
	1pcs	220mA	100mA
	2pcs	180mA	100mA
Charge Time (estimated.)	Ni-MH AA (2600mAh)	1-2 batteries	1.45 hours
	Ni-MH AA (2100mAh)	1-2 batteries	1.17 hours
	Ni-MH AAA (300mAh)	1-2 batteries	0.34 hours
	Ni-MH AAA (900mAh)	1-2 batteries	1 hours
Charge Protection	Reverse polarity protection (wrong insertion), Overheat and Short-circuit Protection.		
Approvals	CE, RoHS		

The Data in this publication represents product tested under the conditions specified. They do not represent standards or specifications which must be met. Strand reserves the right to change and improve product characteristics at any time. Contents herein do not constitute a warranty.